



(19)

(11) Publication number: 58088007 A

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 56185527

(51) Intl. Cl.: B01D 13/00 B01D 1/00

(22) Application date: 20.11.81

<p>(30) Priority:</p> <p>(43) Date of application publication: 26.05.83</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: ASAHI GLASS CO LTD.</p> <p>(72) Inventor: MIYAKE HARUHISA SUGAYA YOSHIO ASAWA TATSURO</p> <p>(74) Representative:</p>
--	--

(54) SEPARATION OF LIQUID MIXTURE

(57) Abstract:

PURPOSE: To use a high molecular membrane obtained from a solution prepared by dissolving a carboxylic acid type fluorinated copolymer in a hydrophilic org. solvent, in a method for separating a mixture containing an org. liquid according to vapor separation.

CONSTITUTION: In separating or concentrating a mixture comprising org. liquids or an org. liquid and water according to vapor separation, when a high molecular membrane, which is formed from a solution prepared by dissolving a copolymer consisting of a fluorinated ethylenic monomer and a carboxylic acid group containing ethylenic monomer (pref., fluorine contained one) in a hydrophilic org. solvent containing a small amount of water, is used, the efficiency of separation or concn. is enhanced and a permeation speed is also made fast. A separation temp. is selected from a

range of 0W200°C and pressure from a
range of vacuum W100kg/cm2.

COPYRIGHT: (C)1983,JPO&Japio